

Auto-Dialers



COMBI BASIC

Auto-Dialer with din bar to be installed in the control panel.

MAIN FEATURES

- Protocols Management for call-center (ex. Ademco Contact ID).
- Simplified wiring system for speaker modules (SPEAKERLIFT) 2 wires.
- Outputs for light signals management: sent and acknowledged alarm signals.
- GSM line input with COMBI GSM device (optional).
- Programming by telephone keypad; locally and remotely.
- Programming via Cloud (only with COMBI GSM).
- Memory capacity up to 10 phone numbers.
- 32 customizable messages divided into 4 languages.
- Inductive loop facility for the hard-of-hearing.
- 4 types of inputs: alarm input, alarm filter input, technical alarm input and reset alarm input.
- Low battery level alarm.

SIZE
111x92x50 mm

TECHNICAL DATA

Input power supply: from 11V to 14V DC.
Output power supply: 12V DC 500 mA.

Inputs: 4x opto isolator 5-50V 50mA.
Outputs: 2 open collectors.

EXPANSION BOARDS



CB LINE

Analog line interface.

MAIN FEATURES

- PSTN analog line input.



CB RELE

Relay board.

MAIN FEATURES

- 2 Relay outputs for piloting locally and remotely.

CB BAT

UPS board.

MAIN FEATURES

- Allows for supply Auto-Dialer with voltage between 9 and 24 V AC/ DC.
- Power supply filter against interferences.
- 12 V rechargeable battery input.
- Battery charger function.
- Efficiency battery monitoring.
- Technical alarms management: low and /or inefficient battery, no electricity.